



Models 881 / 882

Incredible Performance, Practical Design, and Vulcan's Patented Strapless Wheel Lift System

The 880 Series has one of the highest customer satisfaction levels in the industry due to its practical design and incredible performance. Features such as independent control stations for the wheel lift and boom functions provides for easier operation and increased safety, a durable cross bar and pivot pin system with longer life than conventional systems found on competitors products and most of all Vulcan's patented strapless wheel lift system. The unique system is one of the most user friendly systems in the industry, allowing the wheel retainer to pivot horizontally as well as vertically for easy hookup in virtually any situation, even when the wheels are turned or obstructed and best of all you have a safe and easy hookup with no tie down straps. Call your local Vulcan Distributor to find out why your next towing & recovery unit should be a Vulcan.

Note: Some optional equipment may be shown. Other Vulcan Towing and Recovery Equipment is available from your local Vulcan Distributor.

VULCAN MODELS 881/882 - STANDARD FEATURES

Vulcan's Patented 4,000 lb. Wheel Retainer Wheel Lift System
 16,000 lb. Boom Retracted
 60" Cab to Axle Steel Body
 Body Width 86" (90" optional)
 Safety Chain Guards
 Wheel Lift Safety Chains
 Independent Wheel Lift Tilt
 Mud Flaps

Dual Wheel Lift Control Stations Located at the Tail Board
 Hydraulic Pump
 Free Spool Handles
 Cable Tensioners
 Tail Board Chain Pockets for Safety Chains
 Wheel Retainer Storage Pockets Built into Body
 3/8" x 100' Winch Cables
 Drivers and Passenger Side Tool Compartments

VULCAN MODELS 881/882 - OPTIONAL EQUIPMENT

90" Body Width
 Spacer Tool Boxes
 Trailer Hitch
 Fenderettes
 Wheel Simulators
 Many Other Popular Vulcan Options

Emergency Lighting
 Dress Up Packages
 P.T.O.
 Light Pylons
 Sling

VULCAN MODELS 881/882 - SPECIFICATIONS

		881	882
Recovery Boom:	Retracted	16,000 lbs.	16,000 lbs.
	Extended at 34° (TEMA)	4,000 lbs.	4,000 lbs.
	Extension Stroke	58"	58"
	Maximum Lift Angle	37°	37°
	Maximum Hook Height	13"	13"
	Reach Past Underlift Lowered	46"	46"
Winch:	881 - Single Worm Gear	8,000 lbs.	8,000 lbs.
	882 - Dual Worm Gear		8,000 lbs.
Cab to Axle: (clear)	Min. (Standard Body)	60"	60"
	Max. (with Spacer Boxes)	84"	84"
Suggested Chassis:	GVWR	15,000 lbs.	15,000 lbs.
Underlift:	Lift Capacity Extended on wheel lift	4,000 lbs.	4,000 lbs.
	Tilt Capacity Fully Extended	4,000 lbs.	4,000 lbs.
	Maximum Reach	66"	66"
	Tow Rating	10,000 lbs.	10,000 lbs.

Note: Model 880 also available with no boom and an optional deck mounted 4 ton winch

Note: Ratings are based on structural factors only--not chassis capacity. Vulcan reserves the right, without notice and without obligation, to improve or modify products, which may change the specifications, models and feature availability. Maximum tire size is 245/70 R19.5.