



**MODELS 892 / 894**

[Standard Features](#)  
[Optional Equipment](#)  
[Description](#)  
[Back to Product Line](#)

## Light Duty Versatility, Medium Duty Performance

In today's competitive business environment, versatility is a key ingredient to your success. The Vulcan 892 and 894 are designed to meet that challenge with the ability to tow a wide variety of vehicles including autos, motorhomes, light trucks and vans. The wheel lift has the ability to lift 6,000 lbs., for heavier loads the underlift is capable of lifting up to 6,500 lbs. at full extension using the standard lift forks.

Separate boom and underlift controls for easy and safe operation, an increased crossbar bearing surface for longer life and reliability along with Vulcan's patented strapless wheel lift system are just a few of the numerous features that distinguish Vulcan as the leader in customer loyalty and satisfaction for towing and recovery equipment. Call your local Vulcan distributor to find out more about how the Vulcan 892 or 894 can increase your profitability.



Equipment Company, Inc.  
 8503 Hilltop Drive,  
 Ooltewah, TN 37363  
 Toll Free: 1-800-489-2401  
 FAX: 1-800-960-6667  
 e-mail: [vulcansales@millerind.com](mailto:vulcansales@millerind.com)

Note: Some optional equipment may be shown. Other Vulcan Towing and Recovery Equipment is available from your local Vulcan Distributor.

[Back to top](#)

<b>VULCAN MODELS 892 / 894 - STANDARD FEATURES</b>	
Vulcan's patented 6,000 lb. wheel retainer wheel lift system	Dual wheel lift control stations located at the tail board
20,000 lb. boom retracted	Hydraulic pump
60" Cab to Axle steel body	Free spool handles
Body width 90"	Dual boom control stations located on deck
2" steel fenderettes	Wheel lift safety chains
Safety chain guards	Tail board chain pockets for safety chains

Independent wheel lift tilt	Wheel retainer storage pockets built into body
Mud flaps	Conventional sling support brackets
FMVSS lighting	Drivers and Passenger side tool compartments
Cable tensioners	1 set of 3" low profile frame forks and holders

[Back to top](#)

<b>VULCAN MODELS 892 / 894 - DESCRIPTION</b>		
	<b>892</b>	<b>894</b>
Boom: Retracted	20,000 lbs.	20,000 lbs.
Extended at 34° (TEMA)	5,000 lbs.	5,000 lbs.
Maximum lift angle	37°	37°
Maximum boom height	13'	13'
Reach past Tailboard lowered	76"	76"
Winch: Winch (Worm Gear)	8,000 lbs.	10,000 lbs.
Cable: Per winch	3/8" x 100'	7/16" x 100'
Cab to Axle (clear) Min. (Standard body)	60"	60"
Max. (with spacer boxes)	108"	108"
Suggested chassis GVWR	18,000 lbs.	18,000 lbs.
Underlift:		
Lift capacity extended with forks	6,500 lbs.	6,500 lbs.
Lift capacity extended on wheel lift	6,000 lbs.	6,000 lbs.
Tilt capacity fully extended with forks	6,500 lbs.	6,500 lbs.
Maximum reach to center of forks	65"	65"
Tow Rating	20,000 lbs.	20,000 lbs.

[Back to top](#)

<b>VULCAN MODELS 892 / 894 - OPTIONAL EQUIPMENT</b>			
Emergency lighting	Spacer tool boxes	Dress up packages	Sling
Trailer hitch	P.T.O.	3" or 4" Fenderettes	Light pylons
Wheel simulators	Other lifting attachments		
Many other popular Vulcan options			

[Back to top](#)

Note: Ratings are based on structural factors only--not chassis capacity. Vulcan reserves the right, without notice and without obligation, to improve or modify products, which may change the specifications, models and feature availability. Maximum tire size is 245/70 R19.5.