



MODELS 896 & 897

Designed to Meet the Demanding Needs of Today's Professional Operator

Your business depends on a wide range of road service applications. The Vulcan 896/897 Medium Duty Series offers you the power, versatility and dependable performance to satisfy that wide range of requirements such as motor homes, delivery vans and autos.

The separate boom and underlift controls along with Vulcan's patented strapless wheel lift hook up are just a few of the user friendly features that sets Vulcan far ahead of the competition.

For more information on how the Vulcan 896/897 can help meet your demands and increase your profit contact your local Vulcan distributor.

Note: Some optional equipment may be shown. Other Vulcan Towing and Recovery Equipment is available from your local Vulcan Distributor.

VULCAN MODELS 896/897 - STANDARD FEATURES

<ul style="list-style-type: none"> Vulcan's Patented 6,500 lb. Wheel Retainer Wheel Lift System Tandem Hydraulic Pump Body Width 94" Free Spool Handles Cable Tensioners Independent Wheel Lift Tilt Wheel Lift Safety Chains Mud Flaps FMVSS Lighting 84" Cab To Axle Steel Body with 2 Tool Compartments Per Side (Tunnel on Front Compartment) 	<ul style="list-style-type: none"> Dual Wheel Lift Control Stations Located at the Tail Board Dual Lift Cylinders on Recovery Boom Dual Hydraulic Tanks on 897 Tail Board Chain Pockets for Safety Chains Wheel Retainer Storage Pockets Built into Body Dual Boom Control Stations Located on Deck 2" Steel Fenderettes Safety Chain Guards Conventional Sling Support Brackets 1 Set of 3" Low and 1 Set of 3" High Profile Frame Forks and Holders
---	---

VULCAN MODELS 896/897 - OPTIONAL EQUIPMENT

<ul style="list-style-type: none"> Emergency Lighting Dress Up Packages Trailer Hitch 3" or 4" Fenderettes Wheel Simulators 6,000 lb. Car Wheel Retainers 	<ul style="list-style-type: none"> 24" or 36" Spacer Tool Boxes Sling P.T.O. Light Pylons Other Lifting Attachments Many Other Popular Vulcan Options
---	---

VULCAN MODELS 896/897 - SPECIFICATIONS

		896	897
Recovery Boom:	Retracted	24,000 lbs.	28,000 lbs.
	Extended at 34° (TEMA)	10,000 lbs.	12,000 lbs.
	Maximum Lift Angle	34°	34°
	Maximum Hook Height	149"	149"
	Reach Past Tailboard Lowered	76"	76"
Winch:		Planetary - 12,000 lbs.	Worm Gear - 14,000 lbs.
Cable:	Per Winch	150' x 7/16"	150' x 1/2"
Cab to Axle: (clear)	Min. (Standard Body)	84"	84"
	Max. (with Spacer Boxes)	132"	132"
Suggested Chassis:	GVWR (minimum)	25,000 lbs.	25,000 lbs.
Underlift:	Lift Capacity Extended with Forks	8,000 lbs.	8,000 lbs.
	Lift Capacity Extended on Wheel Lift	6,500 lbs.	6,500 lbs.
	Lift Capacity Fully Retracted with Forks	10,000 lbs.	10,000 lbs.
	Maximum Reach to Center of Forks	72"	72"
	Tow Rating	26,000 lbs.	26,000 lbs.

Note: Ratings are based on structural factors only--not chassis capacity. Vulcan reserves the right, without notice and without obligation, to improve or modify products, which may change the specifications, models and feature availability. Maximum tire size is 245/70 R22.5.