



Steel & Aluminum Carriers

Enduring Value for Your Demanding Business

Vulcan Steel & Aluminum Carriers are designed to meet the demands of our highly competitive industry. An industry where reliability, value and high quality are essential. The Vulcan Carriers are packed with practical, quality features like the popular Vulcan Wheel Lift System. Best of all, the Vulcan Carriers are backed by an extensive network of service professionals.

Call 1-800-489-2401 for more information on the Steel & Aluminum carrier series or the complete line of Vulcan quality towing and recovery equipment.

Note: Some optional equipment may be shown. Other Vulcan Towing and Recovery Equipment is available from your local

Vulcan Distributor

VULCAN STEEL & ALUMINUM CARRIERS - STANDARD FEATURES

Lighted Dual Controls
 Mechanical Tilt Lock Out System
 4 Ton Winch 2/50' of 3/8" Winch Cable
 Full Length Slide Pads
 Dual Outboard Holddown System
 Full Height Cab Protector
 Front Chain Trays
 Dual Lift Cylinders
 6 Tie Downs

Mud Flaps
 FMVSS Lighting
 Free Spool Handle
 Install Kit
 Cable Level Winder
 Cable Roller Guide
 Hydraulic Pump
 2 Safety Chains

VULCAN STEEL & ALUMINUM CARRIERS - OPTIONAL EQUIPMENT

Independent Strapless Wheel Lift System
 Safety Lighting
 Wheel Simulators
 P.T.O.
 Tie Down Chains
 Additional Crossmembers (Steel Only)
 Trailer Ball Adapter

L arms in lieu of wheel retainers
 Switch Panel
 Tool Compartments
 "V" Bridle
 Removable Rails
 Stationary Cab Protector (Requires 10" Additional C.A.)
 Many Other Popular Vulcan Options

VULCAN STEEL & ALUMINUM CARRIERS - SPECIFICATIONS

DESCRIPTION	ALUMINUM			HEAVY DUTY STEEL		
	17 1/2'	19'	21'	17 1/2'	19'	21'
Outside Bed Width	95"	95"	95"	95"	95"	95"
Bed & Body						
Capacity-Distributed Load	8,000 lbs.	10,000 lbs.	10,000 lbs.	8,000 lbs.	10,000 lbs.	10,000 lbs.
Bed Size	17' 6"	19'	21'	17' 6"	19'	21'
Bed Surface	Aluminum Alloy Extrusion			Steel Diamond Plate		
Cab to Axle						
Conventional	108"	118"/122"	138"/142"	108"	118"/122"	138"/142"
Cabover	112"	127" *	144"/150"	112"	127" *	144"/150"
Recommended Chassis						
GVW Minimum	10,000	15,000	15,000	10,000	15,000	15,000

GVW Maximum	15,000	25,500	25,500	15,000	25,500	25,500
Tow Bar						
Lift Rating (lbs.)	2,000	2,000	2,000	2,000	2,000	2,000
Tow Rating (lbs.)	5,000	5,000	5,000	5,000	5,000	5,000
Independent Wheel Lift						
Lift Rating (lbs.)	N/A	2,500	2,500	N/A	2,500	2,500
Tow Rating (lbs.)	N/A	6,250	6,250	N/A	6,250	6,250

* A 19.6" body is available and recommended for cabover chassis with a 127" CA.

Note: Ratings are based on structural factors only--not chassis capacity. Load rating is based on equally distributed load over entire bed surface; i.e., water level load.
Vulcan reserves the right, without notice and without obligation, to improve or modify products, which may change the specifications, models and feature availability.